



Declaration of performance and CE marking

(Regulation No 305/2011/EU)

- 1. Unique identification code of the product-type: Porcelain tiles with "TOPCER" marking.
- 2. Product type: Dry pressed porcelain tiles (EN 14411 Annex G Group BIa).
- 3. Intended use: For internal or external wall and floorings.
- 4. Manufacturer: TopCer Indústria de Cerâmica, S.A. Zona Industrial de Oiã 3770 068 Oiã PORTUGAL
- 5. Authorized representatives: None
- 6. System of assessment and verification of constancy of performance: System 4
- 7. Construction product covered by harmonized standard: EN 14411 Annex G Group BIa.
- 8. European technical assessment: None
- 9. Declared performance:

C C E EN 14411:2012 Dry pressed porcelair For internal or external		
Essential characteristics	Performance	Test method
Reaction to fire	Class A1 / A1 _{FL}	Decision 96/603/CE
Breaking strength Modulus of rupture	> 1300 N R > 35 N/mm ²	EN ISO 10545-4
Thermal shock resistance	Passed	EN ISO 10545-9
Bond strength / adhesion	 a) With cementitious adhesives: 2.0 N/mm² b) With dispersion adhesives: 1.6 N/mm² c) With reaction resin adhesives: > 2.8 N/mm² 	EN 1348
Slipperiness	https://topcer.com/general_data.php	
Durability Freeze/thaw resistance	Passed	EN ISO 10545-12
Release of dangerous substances:		
LeadCadmium	NPD NPD	EN ISO 10545-15

NPD=No performance determined.

10. The performance of TopCer products identified in points 1 and 2 is in conformity with the declared performance in point 9, for intended use specified in point 3. This declaration of performance authorizes CE marking and is issued under the sole responsibility of the manufacturer identified in point 4, based on initial type tests made at CTCV - Portugal, regular tests at independent laboratories and factory production control in conformity with ISO 9001 and ISO 14001 standards. For different applications, please, contact TopCer.

Test reports available at: <u>https://topcer.com/general_data.php</u>

Signed for and on behalf of the manufacturer by:

The Managing Director

TopCer, 2023-10-20